



## Practical training trolley

### product features

#### Integrated smart teaching terminal

21.5 Inch high-definition touch screen, integrated recording, interaction and control functions. Built-in professional microphone array, support 360° omnidirectional pickup.

#### Mobile teaching solutions

Built-in large capacity power supply, support for mobile teaching scenarios. Real-time power display, 6 hours of long battery life.

#### Intelligent classroom interaction system

#### Professional teaching video recording

Teacher broadcast function, one-click push the main screen to the group screen. Support group discussion, screen sharing and other interactive teaching.

Dual-way 10x zoom camera, accurately capture the blackboard, experimental details. 2 megapixel high-definition picture quality, perfect presentation of teaching demonstration.

#### Easy deployment and use

4 The road PoE power supply, a network cable to solve the power transmission. Support wireless image transmission, flexible arrangement of teaching space.

#### Intelligent teaching management

1TB large storage, complete record of teaching process. Support course playback, key marking, after-class review.

#### Distance interactive teaching

Built-in interactive 4.0 system, supports remote classroom access. It can realize cross-campus and cross-region teaching resource sharing.

#### Future expansion space

Modular design, support for functional expansion. Compatible with all kinds of educational information equipment.

## Live recording host

screen size	21.5 Inch high-definition LCD integrated touch screen
HDMI IN	*1 Support 1080P60
HDMI OUT	*2 Support 1080P60
LINE IN	*2 3.5mm
LINE OUT	*1 3.5mm
RJ45	*5 of which have POE capability
memory	1T

## cell


Main output voltage	12±0.5V
Main output current	10A
USB	×2 USB1: Output voltage 5±0.2V USB2: Output current 3A
charging voltage	14.6-16V
charging current	≤10A
chassis	Q235 Sheet metal, white paint

## HD close-up camera\* 2

imaging sensor	1/2.8 inch CMOS
focal distance	4.7-47mm
iris diaphragm	F1.6-F3.0
scanning mode	non interlaced
Optical zoom	10 times
lens system	58.6°-6.4°
shutter speed	1/25s to 1/100,000s
white balance	Auto/manual lock white balance

## product size

\* The following sizes are for reference only and do not represent the final standard. Please contact us for specific sizes required

Contact Us:  
[sales@amdox.com](mailto:sales@amdox.com)Facebook:  
[Sunvol Board](#)YouTube:  
[SUNVOL](#)Website:  
[www.amdox.com](http://www.amdox.com)